



Powertron 10W-40 Synthetic Blend Petrol Engine Oil

TECHNICAL DATA SHEET

Product Description

Veedol Powertron 10W-40 is a specially formulated engine oil with synthetic technology meeting stringent performance specifications for naturally aspirated and turbo charged petrol and diesel engines working under normal and arduous conditions.

Performance Specifications

Veedol Powertron 10W-40 meets the following performance requirements:

- API: SL
- ACEA: A3/B3
- MB: 229.1/227.5
- VW: 500.00/505.00

Features & Benefits

- Excellent High and Low Temperature Performance.
- Improved Fuel Efficiency and Low Emissions.
- Advanced oil Performance and Reduced Consumption.
- High Levels of Engine Cleanliness.
- High Temperature Protection against Ring Sticking and corrosion.

Typical Properties

Typical Properties Test Parameters	ASTM Method	Typical Values
Density @ 15°C, Kg/L	D 4052	0.88
Kinematic Viscosity, @ 100°C, cSt	D 445	13.8
Viscosity Index	D 2270	148
Total Base Number, mg KOH/gm	D 2896	8.5
Pour Point, °C	D 97	-32
Flash Point (COC), °C	D 92	214

Properties mentioned above are typical only, and minor variations which do not affect the product performances, are to be expected in normal manufacturing.

فييدول إنترناشيونال د.م.س.س

VEEDOL INTERNATIONAL DMCC

وحدة رقم 1501 | إنديغو آيكون | أرض رقم إف 3 | أبراج بحيرات الجميرا | دبي | الامارات العربية المتحدة | تليفون: +971 4 3688 416 | فاكس: +971 4 3688 418
Unit No. 1501 | Indigo Icon | Plot No. F3 | Jumeirah Lakes Towers | P.O. Box No. 117019 | Dubai | United Arab Emirates
رقم الرخصة ٣٢٠٥١ DMCC رقم السجل التجاري ٣٠٠٢ DMCC
Tel: +971 4 3688 416 | Fax: +971 4 3688 418 | Email: enquiry@veedol.ae | www.veedol.ae
Licence No. DMCC-32051 | Registration No. DMCC3002
Company is registered & Licensed as a FREEZONE Company under the Rules & Regulations of DMCCA