



SYNTRON 0W-20

Fully Synthetic Premium Multigrade Engine Oil

TECHNICAL DATA SHEET

Product Description

Veedol Syntron 0W-20 is an advanced fully synthetic low viscosity engine oil formulated for fuel efficiency. It provides excellent wear protection under the most extreme circumstances even at cold start up. This viscosity of oil may not be suitable for use in certain engine types, please refer to the owner manual or handbook.

Performance Specifications

Veedol Syntron 0W-20 meets the following performance requirements:

- API: SN
- ACEA: A5/B5
- ILSAC: GF-5

Features & Benefits

- Fully synthetic low viscosity fuel efficient engine oil.
- Ideal for petrol and hybrid engines.
- Superior protection against sludge formation and combustion contamination.
- High level of engine cleanliness.

Typical Properties

Typical Properties Test Parameters	ASTM Method	Typical Values
Density @ 15°C, Kg/L	D 4052	0.85
Kinematic Viscosity, @ 100°C, cSt	D 445	7.5
Viscosity Index	D 2270	158
Total Base Number, mg KOH/gm	D 2896	8
Pour Point, °C	D 97	-42
Flash Point (COC), °C	D 92	224

Properties mentioned above are typical only, and minor variations which do not affect the product performances, are to be expected in normal manufacturing.

فيدول إنترناشيونال د.م.س.س

VEEDOL INTERNATIONAL DMCC

وحدة رقم 1501 | إنديغو آيكون | أرض رقم إف 3 | أبراج بحيرات الجميرا | دبي | الامارات العربية المتحدة | تليفون: +971 4 3688 416 | فاكس: +971 4 3688 418
Unit No. 1501 | Indigo Icon | Plot No. F3 | Jumeirah Lakes Towers | P.O. Box No. 117019 | Dubai | United Arab Emirates

رقم الرخصة ٣٢٠٥١ DMCC | رقم السجل التجاري ٣٠٠٢ DMCC

Tel: +971 4 3688 416 | Fax: +971 4 3688 418 | Email: enquiry@veedol.ae | www.veedol.ae

Licence No. DMCC-32051 | Registration No. DMCC3002

Company is registered & Licensed as a FREEZONE Company under the Rules & Regulations of DMCCA