MULTIGEAR EXPRESS API GL-5 SAE 85W-140

EXTREME PRESSURE GEAR & TRANSMISSION OIL

GO

TECHNICAL DATA SHEET

Product Description

Veedol Multigear ExPress 85W-140 is premium multi-grade automotive gear oil with Extreme Pressure additives. Processed from premium virgin base oils, it offers excellent thermal and oxidation stability. It provides excellent protection to gears and other components even under heavy duty conditions.

Veedol Multigear ExPress 85W-140 exceeds requirements of API GL-5 and is recommended for heavily loaded rear axles of Trucks, Buses, LCVs, MUVs and Cars.

High viscosity index oil maintains high fluidity at low temperatures and retains higher viscosity at high temperatures. Veedol Multigear ExPress 85W-140 also aids fuel economy.

Typical Properties:

Test Parameters	ASTM Method	Typical Values
Density @15 ºC, Kg/l	D 4052	0.910
Kinematic Viscosity @ 100 ºC, cSt	D 445	26
Viscosity Index	D 2270	95
Flash Point, ºC	D 92	220
Pour Point, ºC	D 97	-15

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing.

VEEDOL INTERNATIONAL DMCC
Unit No.1501| Indigo Icon I Plot No. F3 I Jumeirah Lakes Towers
P.O. Box No. 117019 I Dubai I United Arab Emirates
Tel: +971-4-3688416 I Fax: +971-4 3688418 E-mail : enquiry@veedol.ae
www.veedol.ae