



POWERTRON 10W-40 SN

Advanced Multigrade Engine Oil

TECHNICAL DATA SHEET

Product Description

Veedol Powertron 10W-40 SN is a advanced high performance semi synthetic oil suitable for petrol and diesel engines including turbo, fuel injection and vehicles fitted with catalytic converters.

Performance Specifications

Veedol Powertron 10W-40 SN meets the following performance requirements:

- API: SN
- ACEA: A3/B4
- MB: 229.3
- VW: 502.00, 505.00
- Renault: RN0700/RN0710

Features & Benefits

- Ensures lubricant performance.
- Excellent high & low temperature performance.
- Outstanding fuel efficiency.
- Effective environmental protection.

Typical Properties

Typical Properties Test Parameters	ASTM Method	Typical Values
Density @ 15°C, Kg/L	D 4052	0.86
Kinematic Viscosity, @ 100°C, cSt	D 445	14.5
Viscosity Index	D 2270	164
Total Base Number, mg KOH/gm	D 2896	13
Pour Point, °C	D 97	-34
Flash Point (COC), °C	D 92	222

Properties mentioned above are typical only, and minor variations which do not affect the product performances, are to be expected in normal manufacturing.

فيدول إنترناشيونال د.م.س.س

VEEDOL INTERNATIONAL DMCC

وحدة رقم 1501 | إنديغو آيكون | أرض رقم إف 3 | أبراج بحيرات الجميرا | دبي | الامارات العربية المتحدة | تليفون: +971 4 3688 416 | فاكس: +971 4 3688 418
Unit No. 1501 | Indigo Icon | Plot No. F3 | Jumeirah Lakes Towers | P.O. Box No. 117019 | Dubai | United Arab Emirates

رقم الرخصة ٣٢٠٥١ DMCC | رقم السجل التجاري ٣٠٠٢ DMCC

Tel: +971 4 3688 416 | Fax: +971 4 3688 418 | Email: enquiry@veedol.ae | www.veedol.ae

Licence No. DMCC-32051 | Registration No. DMCC3002

Company is registered & Licensed as a FREEZONE Company under the Rules & Regulations of DMCCA