



POWERTRON SUPER 20W-50

Advanced Synthetic Blend Multigrade Engine Oil

TECHNICAL DATA SHEET

Product Description

Veedol Powertron Super 20W-50 is a premium high performance advanced synthetic blend multigrade engine oil engineered with latest in lubricant additive technology that performs in the toughest conditions. Veedol Powertron Super 20W-50 is suitable for use in passenger cars and commercial vehicles requiring this grade and specification of lubricant.

Performance Specifications

Veedol Powertron Super 20W-50 meets the following performance requirements:

- API: SM
- ACEA: A3/B4
- MB: 229.1

Features & Benefits

- Provides optimum performance and engine protection at extreme temperature.
- Excellent piston deposit control.
- Superior protection against sludge formation and combustion contamination.

Typical Properties

Typical Properties Test Parameters	ASTM Method	Typical Values
Density @ 15°C, Kg/L	D 4052	0.87
Kinematic Viscosity, @ 100°C, cSt	D 445	19.17
Viscosity Index	D 2270	130
Total Base Number, mg KOH/gm	D 2896	10.3
Pour Point, °C	D 97	-30
Flash Point (COC), °C	D 92	234

Properties mentioned above are typical only, and minor variations which do not affect the product performances, are to be expected in normal manufacturing.

فيدول إنترناشيونال د.م.س.س

VEEDOL INTERNATIONAL DMCC

وحدة رقم 1501 | إنديغو آيكون | أرض رقم إف 3 | أبراج بحيرات الجميرا | دبي | الامارات العربية المتحدة | تليفون: +971 4 3688 416 | فاكس: +971 4 3688 418 | Unit No. 1501 | Indigo Icon | Plot No. F3 | Jumeirah Lakes Towers | P.O. Box No. 117019 | Dubai | United Arab Emirates

رقم الرخصة ٣٢٠٥١ DMCC | رقم السجل التجاري ٣٠٠٢ DMCC
Tel: +971 4 3688 416 | Fax: +971 4 3688 418 | Email: enquiry@veedol.ae | www.veedol.ae
Licence No. DMCC-32051 | Registration No. DMCC3002

Company is registered & Licensed as a FREEZONE Company under the Rules & Regulations of DMCCA