

SYNTRON 5W-40

Fully Synthetic Premium Multigrade Engine Oil

TECHNICAL DATA SHEET

Product Description

Veedol Syntron 5W-40 is a fully synthetic engine oil for today's high performance engines, including multi-valve, fuel injection and turbo charged petrol and diesel engines where specified. This oil is NOT suitable for vehicles that have exhaust after treatment devices fitted.

Performance Specifications

Veedol Syntron 5W-40 meets the following performance requirements:

API: SN

ACEA: A3/B4

MB: 229.3/229.5/226.5

• BMW:LL-01

Renault: RN0700/RN0710

VW: 502.00, 505.00PSA: B71 2296

Porsche: A40

Features & Benefits

- Ensures lubricant performance over extended drain intervals
- Excellent high & low temperature performance
- Outstanding fuel efficiency
- Effective environmental protection

Typical Properties

Typical Properties Test Parameters	ASTM Method	Typical Values
Density @ 15°C, Kg/L	D 4052	0.85
Kinematic Viscosity, @ 100°C, cSt	D 445	14.1
Viscosity Index	D 2270	157
Total Base Number, mg KOH/gm	D 2896	10.6
Pour Point, °C	D 97	-42
Flash Point (COC), °C	D 92	225

Properties mentioned above are typical only, and minor variations which do not affect the product performances, are to be expected in normal manufacturing.

فيدول إنترناشيونال د.م.س.س

VEEDOL INTERNATIONAL DMCC