UNITRAC 15W-40

HIGH PERFORMANCE UNIVERSAL TRACTOR OIL

TECHNICAL DATA SHEET

Product Description

Veedol Unitrac 15W-40 is Universal Tractor Oil (STOU) designed for a wide variety of applications for modern Agriculture equipments. It is a fine blend of high viscosity index base oils and an advanced additive package designed to give reliable performance in a wide range of farming applications.

Performance Specifications

Veedol Unitrac15W-40 meets the performance requirements of the following:
API: CG-4/SF/GL-4
ACEA: E3
ZF TE-ML 06A,06B (inc.06R),06C,07B
Sperry Vickers/Eaton: I-280-S
Ford M2C 159B/C , Ford M2C 134D
John Deere J20C, J27
Massey Ferguson: M1145
CNH MAT 3525,3526

Features/Benefits

- Single product that protects engine, transmission, wet brake, hydraulic and front axles.
- Improved performance , Superior extended machine life & reduced downtime .
- Suitable for wide range of manufactures.
- Suitable for use in manual, Powershifts, CVTs and hydrostatic drives.
- Reduces inventory & cuts downs cost.

Typical Properties

Test Parameters	ASTM Method	Typical Values
Density @ 15ºC, Kg/L	D 4052	0.87
Kinematic Viscosity, @ 100ºC, cSt	D 445	14.8
Viscosity Index	D 2270	140
Flash Point (COC), ºC	D 92	222
Pour Point, ºC	D 97	-33
Total Base Number, mg KOH/gm	D 2896	11

Properties mentioned above are typical only, and minor variations which do not affect the product performances, are to be expected in normal manufacturing.

فيدول إنترناشيونال د.م.س.س

VEEDOL INTERNATIONAL DMCC

وحدة رقم 601 | إنديغو آيكون | أرض رقم إف 3 | آبراج بحيرات الجميرا | دبي | الامارات العربية المتحدة | تليفون: ٩٧١٤٣٦٨٨٤١٦+ | فاكس: ٩٧١٤٣٦٨٨٤١٨+

Unit No. 601 | Indigo Icon | Plot No. F3 | Jumeirah Lakes Towers | P.O. Box No. 117019 | Dubai | United Arab Emirates

رقم الرخصة DMCC ٣٢٠٥١ رقم السجل التجاري DMCC ٣٠٠٢

Tel: +971 4 3688 416 | Fax: +971 4 3688 418 | Email: office@veedol.ae | www.veedol.ae